



Model	MB-30	MB-50	MB-75	MB-100	MB-125	MB-150	MB-200	MB-250
Population Equivalent	30	50	75	100	125	150	200	250
Daily Flow m3/day	3.6	6	9	12	15	18	24	30
Daily BOD kg/day	1.8	3	4.5	6	7.5	9	12	15
Peak flow m3/h	1.8	2.25	2.25	2.25	2.81	3.38	4.5	5.63
Length (m)	3.6	4.2	5.1	5.9	6.8	7.8	9.7	11.9
Width (m)	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Height (m)	2.26	2.26	2.26	2.26	2.26	2.26	2.26	2.26

Standard effluent quality BOD:SS 20:30mg/l or better

Tertiary filtration - available upon request BOD:SS 10:10mg/l or better

- Larger models are available and custom designed to specifications required
- Skids are equipped with ISO certified lifting lugs and fork lifter pockets for ease of mobilisation
- All models are designed to fit in ISO containers for shipping purposes



## **HEAD OFFICE**

## FM Environmental Ltd.

Greenbank Industrial Estate Newry, BT34 2QX, N, Ireland Telephone: +44 [0] 28 302 66616 From ROI Call: 048 302 66616 Fax: +44 [0] 28 302 63233 Email: sales@fmenvironmental.com

www.fmenvironmental.com www.greaseguardian.com www.rainwaterharvesting.ie

## **MALTA OFFICE**

## FM Environmental [Malta] Ltd.

Water Technology House A15B Industrial Estate Marsa, Malta Telephone: +356 2122 6172/3

Fax: +356 2122 6171

Email: fmmalta@fmenvironmental.com

www.fmenvironmental.com www.greaseguardian.com

8			15	90
0	20		5	
0)	6		3	1
Φ		0	-	ð
	~	/-	0	1

Distributor:			